

TATA

Declaration of Performance

(according to regulation EU No 305/2011)

Unique ID code

No. TSSP S235J2 Supplied +AR or +N

Strip S235J2 / 1.0117

Harmonised standard

According to EN 10025-1

Intended use- To b

To be used in - welded, bolted and riveted structures

Manufacturer

Tata Steel UK Limited
Strip Products UK
Port Talbot
South Wales
SA13 2NG
Tel: +44 (0)1639 871111
Website: www.tatasteeleurope.com

Authorised Represntative Mak Denys - Director Quality
Tata Steel
Wenckebachstraat 1.
Velson Noord . 1951 JZ . NL .
PO Box 10.000
IJmuiden
1970 . CA. NL

System of AVCP

System of assessment and verification of constancy of performance of the product System 2+

Notified Body Bureau Veritas Italia S.P.A Inspection Services No. 1370 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Strip Products UK limited.

Signed for and on behalf of the manufacturer by

Martin Brunnock – Director, Strip Products UK Tata Steel UK Limited Declared Performance/s

Essential characteristic	Performance				Harmonised technical specification
Tolerances on dimensions and shape	Dimen		EN 10051		
Yield strength (transverse)			Values Min (MPa)		
	>	<= 16	22	25	
Tensile strength (transverse)	Nominal thickness (mm)		235 Values (MPa)		
(>	<=	min	max	
	-	16	360	510	1
Elongation (transverse)	Nominal t (mr		Valı min (%,		
	>	<=			
		1	1:		
	1	1.5	10		
	1.5	2.5	1°		EN140005 4 0004
	2.5	2.5	19		EN10025-1 2004
	Nominal thickness		Values		+
	(mm)		min (%, 5.65√so)		
	3	16	24		
Impact strength (longitudinal)	J2	3 16 J2		-20°C	
Weldability CEV	Nominal thickness (mm)		Values max (%)		
	>	<=			
	-	16	0.3		
Durability	Nominal t		Valu		
	(mm)		max (%)		
	-	<=16	C:0 Mn: P: 0, S: 0,	1,40 ,025 ,025	
	1	I	Cu: (0,55	



1370

Tata Steel Strip Products UK

13

TSSP S235J2 1370-CPD-1707

EN 10025-1 - 2004

Strip S235J2 / 1.0117

To be used in - welded, bolted and riveted structures

Tolerances on dimensions: Strip EN10051

Elongation:

Tensile Strength:

Yield Strength: EN10025-2

Impact Strength: Weldability:
Durability:

Dangerous Substances: No Performance Determined

Date:- August 2020