

## **Declaration of Performance**

(according to regulation EU No 305/2011)

Unique ID code

No. TSSP S275J0C

Strip S275J0C / 1.0140

Harmonised standard

According to EN 10025-1

Intended use- To be used in - welded, bolted and riveted Structures

Manufacturer

Tata Steel UK Limited Strip Products UK Port Talbot South Wales SA13 2NG Tel: +44 (0)1639 871111

Website: www.tatasteeleurope.com

Authorised representative

Mark Denys - Director Quality
Tata Steel
Wenckebachstraat 1 .
Velson Noord . 1951 JZ .
NL . PO Box 10.000
IJmuiden
1970 . CA. NL

System of AVCP

System of assessment and verification of constancy of performance of the product System 2+

Notified Body Bureau Veritas Italia S.P.A Inspection Services No. 1370 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Strip Products UK limited.

Signed for and on behalf of the manufacturer by:

Martin Brunnock – Director, Strip Products UK Tata Steel UK Limited

Date August 2020

## Declared Performance

Essential characteristic	Performance				Harmonised technical specification
Tolerances on dimensions and shape	Dimensions EN 10051				
Yield strength (transverse)	Nominal thickness (mm)		Values Min (MPa)		
	>	<= 16	27	'5	
Tensile strength (transverse)	Nominal thickness (mm)		Values (MPa)		
	>	٧	min	max	
	-	16	430	580	
	3	16	410	560	
Elongation (transverse)	Nominal thickness (mm)		Values min (%, 80mm)		
	>	<=			
		1	15 16 17 18 19 Values min (%, 5.65√so)		EN10025-1 2004
	1	1.5			
	1.5	2			
	2.5	2.5			
	Nominal t				
	(mr				
	3	16	23		
Impact strength (longitudinal)	JO		27J at +0°C		
		hickness n)	Values max (%)		
	>	<=			
	-	16	0.4		
Durability	Nominal thickness (mm)		Values max (%)		
	- <=16		C:0,18		1
		ι	Mn:		
			P: 0,		
			S: 0,		
			N: 0. Cu: (		
L	1		ou. t	,,,,,	1





1370

Tata Steel Strip Products UK

13

TSSP S275J0C 1370-CPR-1707

EN 10025-1 - 2004

Strip S275J0C / 1.0140

To be used in - welded, bolted and riveted

structures

Elongation Tolerances on dimensions: Strip EN10051

Tensile Strength:

Yield Strength: EN10025-2

Impact Strength: Weldability:
Durability:

Dangerous Substances: No Performance Determined